

Reference Data

Eaton 5SC 500i



Product	Short Description
Eaton 5SC 500i	Protection for tower server, networking and storage, LCD display, 500VA/350W, Line-Interactive with AVR & sinewave output, USB and Serial port + contacts, shutdown software, 4 IEC outlets, replaceable batteries, compact design
EATON Ref	
5SC500i	

Packaging	Size (W x D x H*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	199 x 301 x 295	7.5 kg	1 product / carton	743172045140
Complete pallet	1000 x 1200 x 1040	470 kg	60 cartons / pallet	

Packaging content
1 UPS + 2 IEC output power cords + Eaton Intelligent Power Software CD + USB Cable + Serial Cable + Safety guide + Quick Start + CD with 10-language user manual

Technical Specifications	
Technology	Line interactive HF, Sinewave output
Capacity	500 VA / 350 W
Size (W x D x H*)/Weight	150 x 240 x 210 mm / 6.6 kg
Output Receptacles	4 IEC 10A
Output Voltage / Frequency	230 V (adjustable to 220-230-240V) / 50-60 Hz autosensing
Input Voltage tolerance	184V-276V
Features	Automatic Voltage Regulation via Booster & Fader, Advanced battery monitoring (ABM), Deep discharge protection, Automatic battery test, Replace battery indicator, Cold start, adjustable sensitivity to disturbed electrical networks
Administration	1 USB port + 1 serial RS232 & contacts port
User interface	LCD : access to measures, alarms, status
Warranty	2 years warranty including batteries
Standards	IEC/EN 62040-1 (Safety), IEC/EN 62040-2 class B (EMC), CE, CB report, C-Tick
Quality	Designed, manufactured and marketed under ISO9001 & ISO14001 quality system

Load (%)	5	8	10	20	30	40	50	60	70	80	90	100
Runtime (minutes)	120	93	65	34	21	16,5	13	10,5	8,5	7	6	5

Selling points
<ul style="list-style-type: none"> Reliable and affordable UPS for tower servers, networking, and storage Easy to operate : LCD display Automatic voltage regulation and sinewave output Compact design for easy integration Monitoring & shutdown software for Windows, Linux, ... 1 USB port & 1 Serial + contact port for compatibility with existing or future hardware Advanced Battery Management (ABM) technology to increase battery lifetime Replaceable batteries from front panel

Options	Reference
Warranty +, 3rd year warranty uplift	WP813
Warranty +, 4th year warranty uplift	WP813-4
Warranty +, 5th year warranty uplift	WP813-5

*W x D x H= Width x Depth x Height

Reference Data

Eaton 5SC 750i



Product	Short Description
Eaton 5SC 750i	Protection for tower server, networking and storage, LCD display, 750 VA / 525 W, Line-Interactive with AVR & sinewave output, USB and Serial port + contacts, shutdown software, 6 IEC outlets, replaceable batteries, compact design
EATON Ref	
5SC750i	

Packaging	Size (W x D x H*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	238 x 476 x 308	11.5 kg	1 product / carton	743172045157
Complete pallet	1000 x 1200 x 1065	365 kg	30 cartons / pallet	

Packaging content
1 UPS + 2 IEC output power cords + Eaton Intelligent Power Software CD + USB Cable + Serial Cable + Safety guide + Quick Start + CD with 10-language user manual

Technical Specifications	
Technology	Line interactive HF, Sinewave output
Capacity	750 VA / 525 W
Size (W x D x H*)/Weight	150 x 340 x 210 mm / 10.4 kg
Output Receptacles	6 IEC 10A
Output Voltage / Frequency	230 V (adjustable to 220-230-240V) / 50-60 Hz autosensing
Input Voltage tolerance	184V-276V
Features	Automatic Voltage Regulation via Booster & Fader, Advanced battery monitoring (ABM), Deep discharge protection, Automatic battery test, Replace battery indicator, Cold start, adjustable sensitivity to disturbed networks
Administration	1 USB port + 1 serial RS232 & contacts port
User interface	LCD : access to measures, alarms, status
Warranty	2 years warranty including batteries
Standards	IEC/EN 62040-1 (Safety), IEC/EN 62040-2 class B (EMC), CE, CB report, C-Tick
Quality	Designed, manufactured and marketed under ISO9001 & ISO14001 quality system

Load (%)	5	8	10	20	30	40	50	60	70	80	90	100
Runtime (minutes)	124	100	74	38	23	16,5	12,5	11	9	7	6	5

Selling points
<ul style="list-style-type: none"> Reliable and affordable UPS for tower servers, networking, and storage Easy to operate : LCD display Automatic voltage regulation and sinewave output Compact design for easy integration Monitoring & shutdown software for Windows, Linux, ... 1 USB port & 1 Serial + contact port for compatibility with existing or future hardware Advanced Battery Management (ABM) technology to increase battery lifetime Replaceable batteries from front panel

Options	Reference
Warranty +, 3rd year warranty uplift	WP813
Warranty +, 4th year warranty uplift	WP813-4
Warranty +, 5th year warranty uplift	WP813-5

*W x D x H= Width x Depth x Height

Reference Data Eaton 5SC 1000i



Product	Short Description
Eaton 5SC 1000i	Protection for tower server, networking and storage, LCD display, 1000 VA / 700 W, Line-Interactive with AVR & sinewave output, USB and Serial port + contacts, shutdown software, 8 IEC outlets, replaceable batteries, compact design
EATON Ref	
5SC1000i	

Packaging	Size (W x D x H*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	238 x 476 x 308	12.3 kg	1 product / carton	743172045164
Complete pallet	1000 x 1200 x 1065	389 kg	30 cartons / pallet	

Packaging content
1 UPS + 2 IEC output power cords + Eaton Intelligent Power Software CD + USB Cable + Serial Cable + Safety guide + Quick Start + CD with 10-language user manual

Technical Specifications	
Technology	Line interactive HF, Sinewave output
Capacity	1000 VA / 700 W
Size (W x D x H*)/ Weight	150 x 340 x 210 mm / 11.1 kg
Output Receptacles	8 IEC 10A
Output Voltage / Frequency	230 V (adjustable to 220-230-240V) / 50-60 Hz autosensing
Input Voltage tolerance	184V-276V
Features	Automatic Voltage Regulation via Booster & Fader, Advanced battery monitoring (ABM), Deep discharge protection, Automatic battery test, Replace battery indicator, Cold start, adjustable sensitivity to disturbed networks
Administration	1 USB port + 1 serial RS232 & contacts port
User interface	LCD : access to measures, alarms, status
Warranty	2 years warranty including batteries
Standards	IEC/EN 62040-1 (Safety), IEC/EN 62040-2 class B (EMC), CE, CB report, C-Tick
Quality	Designed, manufactured and marketed under ISO9001 & ISO14001 quality system

Load (%)	5	8	10	20	30	40	50	60	70	80	90	100
Runtime (minutes)	114	86	69	37	23	17,5	13	10,5	8,5	7	6	5

Selling points
<ul style="list-style-type: none"> Reliable and affordable UPS for tower servers, networking, and storage Easy to operate : LCD display 8 IEC outlets Automatic voltage regulation and sinewave output Compact design for easy integration Monitoring & shutdown software for Windows, Linux, ... 1 USB port & 1 Serial + contact port for compatibility with existing or future hardware Advanced Battery Management (ABM) technology to increase battery lifetime Replaceable batteries from front panel

Options	Reference
Warranty +, 3rd year warranty uplift	WP828
Warranty +, 4th year warranty uplift	WP828-4
Warranty +, 5th year warranty uplift	WP828-5

*W x D x H= Width x Depth x Height

Reference Data Eaton 5SC 1500i



Product	Short Description
Eaton 5SC 1500i	Protection for tower server, networking and storage, LCD display, 1500 VA / 1050 W, Line-Interactive with AVR & sinewave output, USB and Serial port + contacts, shutdown software, 8 IEC outlets, replaceable batteries, compact design
EATON Ref	
5SC1500i	

Packaging	Size (W x D x H*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	238 x 498 x 308	16.5 kg	1 product / carton	743172045171
Complete Pallet	1000 x 1200 x 1065	515 kg	30 cartons / pallet	

Packaging content
1 UPS + 2 IEC output power cords + Eaton Intelligent Power Software CD + USB Cable + Serial Cable + Safety guide + Quick Start + CD with 10-language user manual

Technical Specifications	
Technology	Line interactive HF, Sinewave output
Capacity	1500 VA / 1050 W
Size (W x D x H*)/ Weight	150 x 410 x 210 mm / 15.2 kg
Output Receptacles	8 IEC 10A
Output Voltage / Frequency	230 V (adjustable to 220-230-240V) / 50-60 Hz autosensing
Input Voltage tolerance	184V-276V
Features	Automatic Voltage Regulation via Booster&Fader, Advanced battery monitoring (ABM), Deep discharge protection, Automatic battery test, Replace battery indicator, Cold start, adjustable sensitivity to disturbed networks
Administration	1 USB port + 1 serial RS232 & contacts port
User interface	LCD : access to measures, alarms, status
Warranty	2 years including batteries
Standards	IEC/EN 62040-1 (Safety), IEC/EN 62040-2 class B (EMC), CE, CB report, C-Tick
Quality	Designed, manufactured and marketed under ISO9001 & ISO14001 quality system

Load (%)	5	8	10	20	30	40	50	60	70	80	90	100
Runtime (minutes)	145	109	90	41	25	17,5	13	10,5	8,5	7	6	5

Selling points
<ul style="list-style-type: none"> Reliable and affordable UPS for tower servers, networking, and storage Easy to operate : LCD display 8 IEC outlets Automatic voltage regulation and sinewave output Compact design for easy integration Monitoring & shutdown software for Windows, Linux, ... 1 USB port & 1 Serial + contact port for compatibility with existing or future hardware Advanced Battery Management (ABM) technology to increase battery lifetime Replaceable batteries from front panel

Options	Reference
Warranty +, 3rd year warranty uplift	WP828
Warranty +, 4th year warranty uplift	WP828-4
Warranty +, 5th year warranty uplift	WP828-5

*W x D x H= Width x Depth x Height