



Powering Business Worldwide

Powerware 9X55 20-40kVA Extended Batteries

July 2011

MODEL	20			20			30			30			40					
Load kVA	15	15	15	20	20	20	25	25	25	30	30	30	40	40	40	Batteries	Part No.	No. of cabinets
Power Factor	0.7	0.8	0.9	0.7	0.8	0.9	0.7	0.8	0.9	0.7	0.8	0.9	0.7	0.8	0.9			
Rating kW	10.5	12	13.5	14	16	18	17.5	20	22.5	21	24	27	28	32	36			
AUTONOMY IN MINUTES																		
	34	31	27	25	21	18	19	16	13	15	12	10	9	8	6	36 x HRL12110WFR	9X55BATM110C36XX	1
	60	44	40	40	32	30	30	25	20	25	20	17	16	13	11	36 x PWHR12-150W4FR	9X55BATM150C36XX	1
	80	70	60	60	49	42	45	36	32	35	30	27	25	20	16	36 x PWHR12-200W4FR	9X55BATM200C36XX	1
	120	105	90	90	71	64	67	60	48	53	45	41	40	32	27	36 x PWHR12-280W4FR	9X55BATM280C36XX	1
	145	125	105	105	95	80	81	71	62	65	55	49	46	37	32	36 x MRX12320WFR	9X55BATM320D36XX	1
	177	145	125	120	105	95	98	85	70	75	68	60	55	46	40	36 x PWHR12-390W4FR	9X55BATMM390C36XX	1
	220	180	170	165	140	120	130	110	98	105	91	78	75	65	56	36 x PWHR12-500W4FR	9X55BATMM500C36XX	1
	260	240	220	200	180	160	150	140	130	125	115	105	90	80	75	36 x XHRL12620W	9X55BATMM620C36XX	1

Notes:

1. Use 9155 or 9355 prefix when ordering.
2. Battery has a 10 year design life at 25°C, flame retardant container
3. For 20/30kVA UPS use 80 as suffix to part number.
4. For 40kVA UPS use 125 as suffix to part number.

Conditions for autonomy definition:

1. 25°C Ambient
2. EOD Voltage 1.75/1.67V/Cell

Cabinet dimensions:

M = 633W x 822D x 1680H
MM* = 1266W x 822D x 1680H
*Shipped in two parts