







Compatibility List:

Eaton has tested the compatibility of Eaton Power Manager with the following devices and applications.

Note: If a Device doesn't support the Quick Scan feature it can be supervised if "Address Scan" or "Range Scan" operations are performed.

1 Eaton Devices

Eaton equipment designation	Type	Features	Illustration
Network Management Card Minislot SNMP/Web – Network-MS (ex 66102) And associated Environment Sensor	UPS Option Card Eaton Pulsar	Quick Scan Supervision Management Shutdown	
Network Management Card & Modbus/JBus – Modbus-MS (ex 66103) (through Ethernet Network) And associated Environment Sensor 66846	UPS Option Card Eaton Pulsar	Quick Scan Supervision Management Shutdown	
ConnectUPS- Minislot Network Management Card / Network-MS (ex 103006826)	UPS Option Card Eaton Powerware	Quick Scan Supervision Management Shutdown	
ConnectUPS-BD Web /SNMP	UPS Option Card Eaton Powerware	Quick Scan Supervision Shutdown (**)	
ConnectUPS-XSlot Web /SNMP/xHubCard (*)	UPS Option Card Eaton Powerware	Quick Scan Supervision Shutdown (**)	
PXGX2000 (*)	UPS Option Card Eaton Powerware	Quick Scan Supervision Shutdown (**)	
PXGX-UPS Card	UPS Option Card Eaton	Quick Scan Supervision Shutdown	
Eaton Advanced ePDU (Europe = Switched (SW), Advanced Monitored (AM) and Managed (MA) / US= Advanced Monitored (AM) and Managed (MA))	ePDU Integrated Communication Card	Quick Scan (v 1.20) Supervision (v1.20) Management (v 1.25)	
Eaton ePDU Monitored & Advanced Monitored	PDU Integrated Communication Card	Supervision	

Eaton ePDU Managed	PDU Integrated Communication Card	Supervision	
Eaton ePDU Switched	PDU Integrated Communication Card	Supervision	
MGE Switched PDU NM - 68130 / 68134/56132/56134/56136/56138 MGE AmpMeter PDU NM - 68152/ 56134/56144	PDU Integrated Communication Card	Supervision	
MGE Midspan NM - 66892	Midspan Integrated Communication Card	Supervision	
Computers (Windows - Linux) hosting the IPP Shutdown Controller	UPS Proxy (Shutdown Controller)	Quick Scan Supervision Management Shutdown	
MGE Network Management Proxy(Windows) XML-Agent	UPS Proxy (Legacy)	Supervision	
Computers (Windows) hosting the application LanSafe Web View	UPS Proxy (Legacy)	Supervision	
MGE Network Management Card MiniSlot SNMP/Web – 66244 And associated Environment Sensor	UPS Option Card (legacy)	Supervision	
Network Management Card Transverse SNMP/Web – 66074 And associated Environment Sensor	UPS Option Card (Legacy)	Supervision	

(*)With Intelligent Power Manager 1.10, the Eaton Powerware 3 phase UPSs compatibility is officially available according to the following solution:



- **Cards:** ConnectUPS-X v4.30 or PXGX2000 v1.20
- **UPSs:** Blade UPS, PW9155 Dual Phase, PW9355 10-30 kVA, PW9390 40-160kVA, PW9395 225-1100kVA & SBM
- **Known limitation:** PW9315 will not be supported by this 1.10 release.

(**)This feature is only available if you install IPM 1.14 on a computer that is NOT hosting a previous IPM release.

If you have upgraded IPM from 1.XX to 1.14 release and want to use this feature, please proceed as follows:

- => Stop IPM service
- => Remove (or rename) the configuration file: configs/config.js
- => Start IPM service
- => If needed, reconfigure system parameters

2 Applications on Computers

Applications designation	Features	
Computers (Windows/Linux) hosting the application Intelligent Power Protector	Quick Scan Supervision Management	
Computers (Windows/Linux/Mac) hosting the application Network Shutdown Module V3.xx	Quick Scan Supervision Management	





3 Eaton Serial line Devices

Eaton Equipment designation	Connectivity
Eaton Powerware series: 3105, 5110, 5115, 5130, 9130, 9135 and legacy 9120, 9125	USB or RS232
Eaton Powerware series: BladeUPS, 5125, 9155, 9355, 9390, 9395	RS232 only
Eaton Pulsar Series: Evolution 650 / 850 / 1150 / S 1250 / 1550 / S 1750 / 2000 / S 2500 / S 3000 Pulsar 700 / 1000 / 1500 / 1000 RT2U / 1500 RT2U (intl. & US Models) Pulsar M / EX Eaton 5PX Pulsar MX & Pulsar MX Frame 16 U / MX	USB or RS232
Eaton Pulsar Series: EX RT Comet EX RT 1:1 / 3:1 / EX 5 RT (Asia/Pacific)	RS232 only

Notes:

- XSlot-USB Module for Powerware series is unsupported by Intelligent Power® Manager 1.12
- Ellipse ASR 600/750/1000/1500 USBS, Ellipse MAX, Protection Station, Protection Center, NOVA AVR, are currently supported by Personal Solution Pac software.

4 Other Devices

Equipment designation	Card/ proxy	Features	
HP UPS Network Module Minislot (AF465A)	Network Card	Quick Scan Supervision	 invent
Dell Network UPS Card (H910P)	Network Card	Quick Scan Supervision	
IBM UPS Network Management Card (46M4110)	Network Card	Quick Scan Supervision	
APC UPSs	APC Network Management Card	Supervision	
All IETF MIB enabled UPSs (RFC1628) e.g. Liebert, ...		Supervision	STANDARD IETF UPS MIB 1.3.6.1.2.1.33.xx
PowerDsine series 6000	Card		
Servertch sentry models	PDU Integrated Communication Card		