

# iDialog

**1:1** 400-1600 VA



USB  
plug



Plug & Play  
installation

## HIGHLIGHTS

**Compact**

**Silent operation**

**Contemporary design**

**Auto restart**

**Low power consumption**

The iDialog range is the ideal solution for protecting PCs and peripherals in the home and office.

iDialog is easy to install and economic to run for protecting:

- IT equipment such as PCs, Media Centres and peripherals, TVs, Home Cinema systems, Satellite and Digital Terrestrial Receivers and DVD recorders and players;
- xDSL modems and routers;
- Small home appliances.

### Silent operation

The UPS is silent in operation (0dBA) thanks to its use of a fan-less design and high frequency components.

### Advanced communications

PowerShield<sup>3</sup> software allows for the safe shutdown of connected IT systems on mains power supply failure. PowerShield<sup>3</sup> provides efficient and intuitive UPS management using bar chart displays for important operating information.

### Auto restart

The UPS automatically restarts when the mains power supply is restored, after auto power.

### ECO Line environmental protection

With energy savings in mind, the iDialog range features a shut-off button to reduce energy consumption during periods of prolonged inactivity.

MODELS	IDG 400	IDG 600	IDG 800	IDG 1200	IDG 1600
<b>POWER</b>	400 VA/240 W	600 VA/360 W	800 VA/480 W	1200 VA/720 W	1600 VA/960 W
<b>INPUT</b>					
Nominal voltage	220-240 Vac				
Input voltage tolerance frequency	230 Vac (+20/-25%)				
Frequency	50/60 Hz with automatic selection				
<b>OUTPUT</b>					
Voltage during mains operation	230 Vac (+20/-25%)				
Voltage during battery operation	230 Vac (+/- 10%)				
Frequency during battery operation	50 or 60 Hz (+/- 1%)				
Waveform	Pseudo Sinusoidal				
<b>BATTERIES</b>					
Type	VRLA AGM maintenance-free lead based				
Recharge time	6-8 h				
<b>OTHER FEATURES</b>					
Net weight (kg)	3.2	3.4	6.6	6.9	
Gross weight (kg)	3.7	4.1	8.1	8.6	
Dimensions (WxDxH) (mm)	90 x 232 x 192			93 x 310 x 270	
Packaging dimensions (WxDxH) (mm)	138 x 300 x 278			170 x 400 x 370	
Protections	Excessive low battery - overvoltage - short circuit				
Communications	USB			USB + RS232	
Output sockets	4 IEC 320 C13			6 IEC 320 C13	
Standards	EN 62040-1-1 and Directive 2006/95/EC; EN 62040-3 EN 62040-2 and Directive 2004/108 EC				
Certificates	CE				
Operating temperature	0 °C / +40 °C				
Colour	Black				
Altitude and relative humidity	6000 m max altitude, <95% non-condensing				
Standard equipment	2 output power supply cables, 1 USB cable, user manual				

## Features

- Reduced energy consumption and 99% efficiency
- Maximum reliability and protection of PCs thanks to PowerShield<sup>3</sup> monitoring and shutdown software, which can be downloaded free at [www.riello-ups.com](http://www.riello-ups.com)
- Can be installed on PCs with Windows 8, 7, 2008, Vista, 2003, Xp, Linux, Mac OSX and Sun Solaris operating systems
- Small size: With its compact shape, iDialog can be placed anywhere on the desk or in the home.
- Silent: iDialog is also suitable for protecting your non-professional digital

equipment such as home cinema systems, satellite and digital terrestrial receivers and DVD players/recorders.

## 2-YEAR WARRANTY

### AVAILABLE OPTIONS



#### SOFTWARE

PowerShield<sup>3</sup>

## DETAILS

IDG 400  
IDG 600  
IDG 800

IDG 1200  
IDG 1600



SOCKETS WITH UPS PROTECTION (NO BREAK IN POWER IF MAINS FAILS)

SERIAL PORT RS232

USB COMMUNICATION PORT

SAFETY FUSE

FILTERED SOCKETS: PROTECTED AGAINST OVERVOLTAGE ONLY

MAINS INPUT PLUG

DATIDGAI13CREN

[www.poweronaustralia.com.au](http://www.poweronaustralia.com.au)

Power On Australia Pty Ltd | ABN 48 110 752 442 | PH 1300 662 432 | FAX 1300 762 416  
Unit 20, 256-258 Musgrave Road COOPERS PLAINS QLD 4108 (Head Office) | PO Box 2007 SUNNYBANK HILLS QLD 4109