

Eaton 9SX UPS

700 VA – 6 kVA



Reliable power protection for the edge and beyond

Combining reliable double-conversion topology, internal static bypass and an easy-to-ready LCD menu display, the Eaton 9SX UPS provides the highly efficient and reliable power

you expect from a 9-series UPS in a convenient tower form factor. Network, Modbus, Relay and signal input functionality enables integration into a variety of IoT and IIoT applications.

Protect the business you've worked hard to grow:

Reliable power for critical systems

The 9SX offers the robust double-conversion, online power protection needed for medical, light industrial, automation and mission critical IT applications. With zero transfer time to battery, continuous filtering of power, and an internal, automatic static bypass, the 9SX ensures performance and compatibility.

Increased battery life

Eaton offers ABM technology that increases battery service life by 50 percent. ABM uses advanced charging techniques to extend battery life and provides advanced notice before batteries fail.

Get more so you can do more

More power

By providing up to 28 percent more wattage compared to traditional UPSs, the 9SX allows you to connect more devices and leave room for expanding IT systems.

More control

Automate power delivery by utilizing switchable, programmable outlets, without the need of a third party device or PDU. Programmable signal input through the RPO port also enables the UPS to change operating modes in reaction to external events.

Gain efficiencies in your operations

Integrate and standardize communications

Maximize uptime with remote monitoring and management of your 9SX via an Eaton connectivity and software. SNMP, serial, USB, Modbus, and relay options enable integration regardless of the system architecture. Remote Power Off/Remote On Off signal input also manages UPS On/Off state preserving battery life during process shutdown.

Advanced LCD interface

Simplify UPS monitoring with Eaton's advanced LCD display. Easy access to UPS alarm history, energy logs, unit serial numbers and firmware versions enable first time issue resolution right at the source. Eight, user-selectable languages ensure success for global deployments.

Services and support:

Eaton provides from battery replacement to full UPS service plans, including 7/24 UPS service options. Eaton has one of the top service models in the industry.

Eaton 9SX UPS Technical Specifications

- 1 LED indicators
- 2 LCD panel
- 3 Hot swappable batteries



- 4 Slot for management card
- 5 RS-232 port and USB port
- 6 EBM connector
- 7 Standard relay output connector
- 8 Battery detection port Remote
- 9 Power Off (RPO)/Signal Input Connector
- 10 Switchable load groups
- 11 Input



Model 9SX1500 shown here

Technical specifications	700 VA	1000 VA	1500 VA	2000 VA	3000 VA	6000 VA
Rating (VA/W)	700 VA/ 630 W	1000 VA/900 W	1500 VA/1350 W	2000 VA/1800 W	3000 VA/2700 W	6000 VA/5400 W
Format	Tower	Tower	Tower	Tower	Tower	Tower
Electrical characteristics						
Technology	ON-LINE double conversion with automatic bypass and Power factor correction system					
Nominal voltage	200/208/220/240V					
Input voltage range	190-276V without derating (up to 120-276V with derating)			200-276V without derating (up to 140-276V with derating)		180-276V without derating (up to 120-276V with derating)
Input frequency range	40-70Hz, 50/60Hz autoselection, frequency converter mode					
Connections						
Input	1 IEC C14 (10A)	1 IEC C14 (10A)	1 IEC C14 (10A)	1 IEC C14 (10A)	1 IEC C20 (16A)	Ph+N+E Terminal block
Outputs	4 AU (10A) sockets	4 AU (10A) sockets	4 AU (10A) sockets	5 AU (10A) sockets 1 IEC C19 (16A) socket	5 AU (16A) sockets 1 IEC C19 (16A) socket	Ph+N+E Terminal block
Switched outlet group	2 outlet groups					
Batteries						
Typical backup times*	300W	500W	800W	1200W	1800W	2500W
9SX 700	14	7,5				
9SX 1000	24	14	7			
9SX 1000 + 1 EBM/+4 EBM	90/320	56/200	33/120			
9SX 1500	39	23	12	7		
9SX 1500 + 1 EBM/+4 EBM	142/520	85/310	50/179	31/115		
9SX 2000	62	36	22	13	7	
9SX 2000 + 1 EBM/+4 EBM	280/1050	165/620	100/390	65/250	40/160	
9SX 3000	78	45	29	17	10	6
9SX 3000 + 1 EBM/+4 EBM	290/1100	175/630	108/421	68/255	45/168	30/112
	900W	1800W	2700W	3600W	4500W	5400W
9SX 6000	66	28	18	11.5	8	6
9SX 6000 + 1 EBM/+4 EBM	250/1016	111/478	67/250	46/180	35/143	28/112
Battery management	ABM® and Temperature compensated charging method (user selectable), automatic battery test, deep discharge protection, automatic recognition of external battery units					
Communication						
Communication ports	1 USB port + 1 serial RS232 port + 1 mini-terminal block for Remote Power Off + 1 mini-terminal block for Output relay					
Communication slot	1 slot for Network-M2, Network-MS, ModBus-MS or Relay-MS cards					
Operating conditions, standards and approvals						
Operating temepature	0 to 40°C					
Typical noise level	40dB	41dB	43dB	45dB	45dB	46dB
Safety	IEC/EN 62040-1, UL 1778, CSA 22.2					IEC/EN 62040-1
EMC	IEC/EN 62040 -2, FCC Class B, CISPR22 Class B					IEC/EN 62040-2
Approvals & markings	CE /CB report (TUV) / cULus / EAC /RCM					CE/CB report (TUV)/EAC/RCM
Dimensions H x W x D in mm/ Weight						
UPS	252x160x357/11.5kg	252x160x387/14.8kg	252x160x437/18.5kg	346x214x412/33.3kg	346x214x412/33.4kg	575x244x542/65.5kg
EBM	252x160x387/19kg	252x160x387/24.5kg	346x214x412/48.7kg	346x214x412/48.7kg	75x244x542/104.9kg	75x244x542/104.9kg
Customer service and support						
Warranty	2 years					

* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

In the interests of continuous product improvement all specifications are subject to change without notice.



1300 662 435
poweronaustralia.com.au

Power On Australia Pty Ltd - ABN 48 110 752 442

Unit 2/121 Evans Road SALISBURY QLD 4107 (Head Office)

Po Box 5322, Daisy Hill QLD 4127