Intelligent, Integrated Infrastructure Solution in an Enclosure

Features and Benefits

- Fully integrated factory assembled and tested for power, thermal management, rack enclosure, power distribution, monitoring and management, and security for IT applications. No dedicated IT room is required.
- Dust protection and noise insulation Fully closed operation, cold/hot air is circulated within the rack for better temperature and humidity control, expanding lifespan of IT equipment, low noise level. Highly suitable for office environment.
- Highly Efficient Built-in high efficiency UPS and cooling equipment, that uses DC frequency conversion technology for energy savings.
- User-friendly interface Large 7-inch LCD touch panel that allows for easy access to system status/alarms/ setting.
- Fast deployment SmartCabinet™ provides faster deployment and is ready to use from day one, removing the need to build, construct and design computer rooms which dramatically reduces the required deployment period compared to a traditional IT facility build.
- Central Management optional feature of RDU-M that provides central management of SmartCabinet™ at multiple sites.

Applications:

- Branch offices, retail stores, small & medium sized business offices, and telecommunication sites
- Branch locations for government, educational institutions, healthcare, finance, business process outsourcing firms
- Warehouse or mobile sites, where computer/networking room is unavailable
- Manufacturing sites for automation control

SmartCabinet™ is a new approach to providing a complete IT infrastructure solution that contains power, thermal management, enclosure, power distribution, monitoring and infrastructure management all in a simple packaged solution. It is a fully integrated, industry-leading plug-and-play solution with a ready to use IT rack space. It eliminates the need to build complex computer rooms which dramatically improves the speed of system deployment compared to the traditional approach. SmartCabinet™ is pre-configured, pre-installed, and factory tested to ensure system compatibility and is ready to use from day one.





SmartCabinet™ Infrastructure Management Solution



Optional: IT Management



Rack Server Access

Provide at-the-rack access to servers, making software upgrades, troubleshooting and system monitoring convenient and less time consuming.

Remote Server and Serial Management



Providing secure and remote out-ofband connections to the servers and serial ports. This unified approach enables IT administrators a faster method to diagnose, configure or restore equipment to meet SLAs and minimize downtime.

Facility Management



LED Lighting

Low power consumption LED lights that automatically light up when door is opened.



Power Management Unit

Built-in Power Management Unit (PMU) provides MCB to UPS, Cooling unit, PDU, and bypass. It also provides surge protection to SmartCabinet™.



Power Distribution

Outlet switched Power Distribution Unit (PDU) distribute power to IT equipment and turn on emergency fans during power outages.



Touch Panel LCD Display

User-friendly display provide easy access to information for power, thermal management, environments, and security



Airflow Management

Separate cold air and hot air channels to prevent hot exhaust air from circulating to the front of the cabinet.



Temperature / Door Access sensors

Temperature sensors at front (cold aisle) and at rear (hot aisle) report critical environmental information and alarm users if exceeding configurable threshold. The door access sensors at front/rear report alarms on unauthorized access.



Central Management and Monitoring

Provides central management of SmartCabinet™ by monitoring power, thermal, environments, security, and providing user interface thru touch panel LCD display.



UPS and Batteries

5KVA On-line double conversion UPS and battery cabinet ensures clean power feeding to critical IT equipment. It also provides backup power to emergency fans during power outages.



Thermal Management (In-Rack Cooling Unit and Outdoor Condensing Unit)

The thermal unit provides up to 3KW cooling capacity directly to IT equipment. Since SmartCabinet™ is fully sealed, the cool air will only use to cool down critical IT equipment with the highest efficiency. An outdoor unit is included to eject the heat outdoor. Two emergency fans automatically run during power outages ensuring continuous cooling capability.



Water Leak Detection


Water leak sensor provides additional security for critical IT equipment.

Interactive Touch LCD Panel



Large touch panel LCD display provides easy access to all information about power, thermal management, environment, alarms, and settings.

Optional: Centralized Management to all SmartCabinet™ using Rack Data Unit Manager



Traditional Room vs. SmartCabinet™

	SmartCabinet™ Not required
Multi-vendor Design and construction Time-consuming	Not required
Design and construction Time-consuming Fa	
Multiple issues	actory designed and pre-configured
Cost of preparation High	Low
Power distribution Requires wall-mounted DB box Costly	Built-in system Surge suppression included
Site preparation period 2-3 weeks	1 day
Aesthetic Different design, color, sizes, etc.	Integrated design
Area required 10 - 20 sqm	0.7 - 2 sqm
Dust protection Usually not available, High cost	Fully enclosed system, IP5X high protection
Noise level Cooling/UPS equipment may go as high as 65dB Not suitable in office environment Su	Fully enclosed system, uitable for office environment <50dB
Monitoring system Low capability Low integration	Fully Integrated system actory Installed / Connected / Tested
User interface Different interfaces for different equipment One	e integration system for all equipment
Post-sales support Multi-vendors Poor technical support	Single vendor provides full support
Relocation cost High Difficult	Low Easy
Pre-assembled Not possible	Yes
Pre-connected Not possible	Yes
Factory tested Not possible	Yes

Technical Specifications

Rack Size	2000 mm (42U) x 600 mm x 1200 mm
Useable U space	29U
Air Flow Management Panel	5U x 3, 2U x 3, 1U x 2
Maximum depth of equipment	1023 mm
Vertical Cable Management Panel	2
Area	$0.6 \mathrm{m}\mathrm{x}1.2 \mathrm{m}=0.72 \mathrm{m}^2$
Color	RAL7021 Black
IP Marking	IP5X
Display panel	7" Touch Panel LCD
Display Languages	English / Chinese
LED Lighting	2
System Luminance	88lux/1M
UPS Capacity	5,000VA / 4,500W
UPS Backup time	10 minutes @3000W load
or 3 backup time	20 minutes @2000W load
System Input Requirement	Min. 40A Max. 50A, Single Phase
System Frequency	50Hz or 60Hz (2 different models)
Power Distribution Units (PDU)	32A input Switched PDU, 18x C13 + 6x C19
Lightning Protection Surge Suppression	Level 3, 20KA
Maintenance Bypass	Included
Cooling Capacity	1,800W ~ 3,500W, variable speed
Refrigerant	R410A
Emergency fan	Two, one at front bottom and one at rear top
System Management (UPS/Cooling/PDU)	Yes
Temperature Sensor	2
Water Leak Detection	1 piece, 5 meters long
Door Access Sensor	2
Safety Standards	EN 60950-1:2006+A11:2009+A1:2010+A12: 2011+A2:2013
EMC Standards	EN 55022:2010 EN 61000-3-11:2000 EN 55024:2010 EN 61000-3-12:2011
Audible Noise	< 50dB (excluding outdoor unit)
Shipping Weight	438kg
Net Weight	348kg
Warranty	2 years parts warranty at system level (ANZ)

^{*} Emerson Network Power reserves the rights to amend the specification without prior notice

Emerson Network Power Australia & New Zealand

AUSTRALIA

REGISTERED OFFICE:

Suite A, Level 6, 15 Talavera Road, North Ryde, NSW 2113 PO Box 149, Macquarie Park Business Hub, NSW 1670, Australia

Phone: +61 2 9914 2900

+ 61 2 9805 9550

Email: salesenp@emersonnetwork.com.au Website: www.emersonnetworkpower.asia

REGIONAL OFFICE:

Sydney (NSW)

Suite A, Level 6, 15 Talavera Road, North Ryde, NSW 2113,

Australia Phone: 1800 005 161 Emergency Service: 1300 367 686

Canberra (ACT) Unit 5, 164 Gladstone St, Fyshwick, ACT 2609, Australia Phone: 1800 005 161

1300 367 686 Emergency Service:

Melbourne (VIC) Unit 11, 350 Bridge Street, Port Melbourne, VIC 3207, Australia

Phone: 1800 005 161 Emergency Service: 1300 367 686

Brisbane (QLD)

Unit 3, 50 Borthwick Ave, Murarrie Qld 4172, Australia

1800 005 161 Phone: Emergency Service: 1300 367 686

Perth (WA) Unit 3, 10 Main Street, Osborne Park, WA 6017, Australia

1800 005 161 Emergency Service: 1300 367 686

NEW ZEALAND

REGISTERED OFFICE:

Unit 2/14 Burleigh St, Grafton, Auckland 1023, New Zealand

Phone: Fax: Toll Free: +64 9 443 5495 +64 9 444 0066 0800 100 877 Emergency Service: 0800 100 877

REGIONAL OFFICE:

Auckland

Unit 2/14 Burleigh St, Grafton, Auckland 1023, New Zealand

+64 9 443 5495 +64 9 444 0066 Phone: Toll Free: 0800 100 877 Emergency Service:

Christchurch Unit 10/9 Print Place, Middleton, Christchurch 8024 +64 3 339 2060 +64 3 339 2063 Phone: Toll Free: 0800 100 877 Emergency Service: 0800 100 877

Email: salesenp@emersonnetwork.com.au Website: www.emersonnetworkpower.asia

While every precaution has been taken to ensure accuracy and completeness herein, Emerson Network Power assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.

Emerson Network Power and the Emerson Network Power Logo are trademarks of Emerson Electric Co. or one of its affiliated companies. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners.

©2016 Emerson Electric Co. All right reserves ANZ16SOLS – SmartCabinetV7-DS